Applicant: Hugh Sharkey and Gary S. Fanton Attorney's Docket No.: 14170-014001 / 25-31-0017

Serial No.: 08/714,987

Filed: September 17, 1996

Page : 2 of 6

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims:

1-89. (canceled)

90. (currently amended): [[The]] <u>A</u> method <u>of claim 89 of delivering energy, the method comprising:</u>

providing an energy delivery device including a distal portion having a thermally conductive material and a sensor completely enclosed by the thermally conductive material, the sensor being positioned within the thermally conductive material to detect a thermal energy from the selected site and from an adjacent fluid medium;

delivering sufficient energy with the distal portion of the energy delivery device to a selected site to effect a contraction in at least a portion of collagen containing tissue at the selected site;

producing a thermal feedback signal which represents a composite of the thermal energy detected from the selected site of the collagen containing tissue and from the adjacent fluid medium with the sensor; and

adjusting a level of energy delivered by the energy delivery device to at least the portion of the selected site based on the thermal feedback signal,

wherein delivering sufficient energy to the selected site to effect a contraction in at least a portion of collagen containing tissue at the selected site causes fluid medium in a vicinity of the portion of collagen containing tissue to increase in thermal energy, and the method further comprises:

moving the energy delivery device away from the portion of collagen containing tissue at the selected site after delivering sufficient energy; and Applicant: Hugh Sharkey and Gary S. Fanton Attorney's Docket No.: 14170-014001 / 25-31-0017

Serial No.: 08/714,987

Filed: September 17, 1996

Page : 3 of 6

moving the energy delivery device back toward the portion of collagen containing tissue at the selected site, after moving away, and sensing an elevated composite temperature due to the increased thermal energy in the fluid medium.

91. (previously amended): The method of claim 90, wherein at least part of the increased thermal energy in the fluid medium is dispersed through the fluid medium.

92. (previously amended): The method of claim 90, wherein delivering an adjusted level of energy comprises delivering a lower level of energy to reduce overheating of the previously heated portion of collagen containing tissue, the lower level of energy being based on the elevated composite temperature that was sensed.

93. (currently amended): [[The]] A method of claim 89 of delivering energy, the method comprising:

providing an energy delivery device including a distal portion having a thermally conductive material and a sensor completely enclosed by the thermally conductive material, the sensor being positioned within the thermally conductive material to detect a thermal energy from the selected site and from an adjacent fluid medium;

<u>delivering sufficient energy with the distal portion of the energy delivery device to a</u>
<u>selected site to effect a contraction in at least a portion of collagen containing tissue at the selected site;</u>

producing a thermal feedback signal which represents a composite of the thermal energy detected from the selected site of the collagen containing tissue and from the adjacent fluid medium with the sensor; and

adjusting a level of energy delivered by the energy delivery device to at least the portion of the selected site based on the thermal feedback signal,

wherein:

Applicant: Hugh Sharkey and Gary S. Fanton Attorney's Docket No.: 14170-014001 / 25-31-0017

Serial No.: 08/714,987

Filed: September 17, 1996

Page : 4 of 6

delivering sufficient energy to the selected site to effect a contraction in at least a portion of collagen containing tissue at the selected site causes fluid medium in a vicinity of the portion of collagen containing tissue to increase in thermal energy,

producing a thermal feedback signal comprises sensing an elevated composite temperature due to the increased thermal energy in the fluid medium, and

delivering an adjusted level of energy comprises delivering a lower level of energy to reduce stray contractions caused by increased thermal energy in the fluid medium.

94. (canceled).